CG75-NG

Natural Gas CHP Unit

We Produce Green Energy...

Standard Basic Module -Open Type

- Highly efficientgas engine
- Highly reliable AC synchronous alternator
- Gas train
- Exhaust/water heat exchanger
- Water/water heat exchanger
- Heating circulation system
- Advanced engine control system, including: ignition system, detonation control system ,speed control system , air/fuel ratio control system
- Industrial silencer
- Control cabinet and switch cabinet
- Multi-functional control system with simple operation
- Data communication interfaces integrated into control system
- Battery charger
- Automatic oil refilling system
- Island mode or connecting to the grid mode

Structure and control cabinet

Structure type	Open type
Canopy painting	High-class powder coating
Electrical control cabinet	Integrated,IP54
Noise level@1m, dB(A)	89.5
@7m, dB(A)	85.5
@10m, dB(A)	82.5

Dimension and weight

Dimension (LxWxH) , mm	3250X1100 X1650
Weight, kg	2000

Special statement :

1、The technical data are based on natural gas with a lower calorific value of 36MJ/Nm³.The technical data indicated is based on standard conditions according toISO8528/1, ISO3046/1 and BS5514/1.

2、The technical data is measured in standard conditions:
Absolute atmospheric pressure：100kPa
Ambient temperature : 25℃
Relative air humidity : 30%

3、Rating adaptation at ambient conditions acc to DIN ISO 3046/1. The tolerance for the specific fuel consumption is + 5 % at rated output.

4、Technical data above are just for standard product ,and may be subject to change. As this document is used only for presale reference, take the specification supplied by PowerLink before ordering as final.

Power andefficiency @50Hz

Electric power -kW	75	Electric efficiency	37.0%
Heat power-kW	106	Heat efficiency	46.0%
Fuelinput-kW	204	Total efficiency	83.0%

Fuel and emission

Fuel type	Natural gas
Methane number	MN > 80
Excess air factor（Lambda）	1
Fuel consumption @100% load, m³/h	20
Supply gas pressure range, kPa	10~20
Emission without catalytic converter	
NOx , mg/Nm³	<6500mg/Nm³
CO , mg/Nm³	<6500mg/Nm³
HCHO (formaldehyde) , mg/Nm³	<60mg/Nm³
NMHC , mg/Nm³	<150mg/Nm³
Emission with catalytic converter (optional)	
NOx , mg/Nm³	≤ 250

CG75-NG

Natural Gas CHP Unit

We Produce Green Energy...

Standard Basic Module + Acoustic Attenuated Canopy (Optional)

Dimension and Noise Level	
Canopy Size	3500*1100*1650mm
Noise Level@ 1m , dB(A)	76.6
@ 7m , dB(A)	65.1
@ 10m , dB(A)	62.1

- ☐ Modular designed and manufactured for plug and play□ Environmental friendly low emission
- ☐ Small indoor space required for installation□ Low noise does not affect the surrounding environment

CG75-NG

Natural Gas CHP Unit

We Produce Green Energy...

Standard Basic Module + Acoustic Attenuated Container (Optional)

Dimension and Noise Level

Optional container（mm）（customized container modeling serviceavailable）	☐ 7000*2300*2500 ☐ 6058*2438*2591 ☐ 12192*2438*2896 ☐ 12192*3000*2896 ☐ 13500*3000*2896 ☐ 15000*3200*3000
Noise Level@ 1m，dB(A)	74.2
@ 7m，dB(A)	63.1
@ 10m，dB(A)	60.1

☐ Outdoor application enabled, weatherproof and dustproof, corrosion preventive□ Environmental friendly low emission

☐ Modular designed and manufactured for plug and play□ Low noise does not affect the surrounding environment

CG75-NG

Natural Gas CHP Unit

POWERink Power Systems

We Produce Green Energy...

CHP Unit performance data and manufacturing technology

CHP unit model	CG75-NG
Electric output power (kW)	75
Heat output power (kW)	106
CHP unit electric efficiency	36.8%
CHP unit heat efficiency	52.2%
CHP unit total efficiency	89.0%
Hot water production @inlet 70℃/outlet 90℃[t/h]	4
Overload runtime at 1.1xSe(hour)	1
Steady-state voltage deviation	≤±1％
Transient-state voltage deviation	-15％~20％
Voltage recovery time(s)	≤4
Voltage unbalance	1%
Steady-state frequency regulation	±0.5%
Transient -state frequency regulation	±5%
Frequency recovery time(s)	≤3
Steady-state frequency band	0.5%
Recovery time response(s)	0.5
Telephone interference factor(TIF)	≤50
Telephone harmonious factor(THF)	≤2% , as per BS4999

Power and efficiency

Load	100%	75%	50%
Electric power (kW)	75	56	38
Heat power (kW)	106	80	53
Energy input (kW)	204	151	107
Electric efficiency	36.8%	37.2%	35.6%
Heat efficiency	52.2%	53.0%	49.5%
Total efficiency	89.0%	90.2%	85.1%

Manufacturing technolog

- Special welded base frame, inner vibration isolators and design for whole lifting
- With high-class paint, endurable brightness as well resistance against abrasion and defacing
- Installation manual, operation and maintenance manual wiring program

Standards and certificate

- ISO3046 , ISO8528 , GB2820
- BS5000PT99 , AS1359 , IEC34
- ISO9001:2008 quality system certification

AC alternatorperformance data

Alternator brand	Leroy-Somer
Alternator model	LSA44.3S5
Rated output power (kW)	80
Power factor	0.8
Rated current @ 400V and 100% load (A)	144
Excitation system	Brushless
THF (BS EN60034- 1)	<2%
Bearing number	1
Winding material	100% copper
Wiring connection	Star
Rotor insulation class	H
Winding pitch	2/3
A.V.R. model	R438
Voltage fluctuation(no load to full load)	± 0.5%
Housing protection	IP23
TIF (NEMA MG 1-22)	<50
Excitation method	AREP
Rated ambient temperature(℃)	40
Rated stator temperature rise(℃)	125

Voltage	Power
380V	80kW
400V	80kW
415V	80kW
440V	72 kW

CG75-NG

Natural Gas CHP Unit

POWERink Power Systems

We Produce Green Energy...

Efficient gas engine

General data

NO. of cylinders		6
Engine type	4-stroke,natural aspirated, stoichiometric	
Cylinder arrangement		In line
Bore x stroke	mm	108×125
Displacement	L	5.89
Compression ratio		13 : 1
Rated speed	rpm	1500
Rated output power	kW	80
Excess air factor		1
Rotation direction	Anti-clockwise viewed on flywheel	
Ignition timing	°BTDC	18

Cooling system

Coolant refilling capacity	L	14
Max. jacket water operating pressure	kPa	240
Min. jacket water circulation flow	L/min	180
Min. jacket water temperature	°C	80
Max. jacket water temperature	°C	88
Max. jacket water difference(inlet-outlet)	K	6
Coolant type	Mixture of 40％antifreeze and 60％clean fresh water. Lower ambient temperature, higher contentof antifreeze.	

Induction/exhaust system

Exhaust flow(wet)	kg/h	390
Combustion air flow	kg/h	380
Exhaust temperature	°C	440
Max. exhaust back pressure	mbar	40
Max. suction restriction	mbar	15

Fuel control system

Gas train，Including：	ball valves
	filters
	gas pressure gauge
	safety solenoid valves
	constant pressure regulator etc
	gas pressure relief valve

Lubrication system

Max. refilling capacity	L	26
Min. refilling capacity	L	19
Max. consumption	kg/h	0.095
Lubrication oil pump	Gear driven	

Energy balance and gas flow

Load	100%	75%	50%
Mechanical power, kW	80	61	41
Coolant heat, kW	65	60	47
Exhaust heat up to 120°C, kW	41	31	22
Max. radiation heat, kW	8.3	/	/
Energy input, kW	204	151	107
Combustion air flow, kg/h	380	310	194
Fuel consumption, m³/h	20	15	11
Exhaust gas flow,kg/h	390	310	199

Ignition system

Ignition type	Electronic ignition system
Polarity	Negative earth
Spark plug	Separate for every cylinder

PCC-300 control system

Open control system is adopted with touch screen display , and various functions, including: engine protection and control, CHP parallel and grid connection, and CHP control functions,as wellas communication functions， etc.

Main functions

- Engine monitor：coolant, lubrication, exhaust, battery
- Supply gas circuit monitor：pressure,temperature and CH4 content
- Auto paralleling and load share
- Voltage and PF control
- Alternator data：U, I, Hz, kW, kVA, kVAr, PF, kWh, kVAh
- Mains data：U, I, Hz, kW, kVAr, PF
- Modbus communicationprotocol based on RS232 and RS485 interfaces
- SMS message
- Internet connection and USB 2.0 interface
- 10-inch touch screen
- Internet monitor, auto orientation and cloud communication
- 1000 history events log

Advantages

- Accordant with consumer requirement
- Complete control project
- Convenient remote monitor and service
- Simplified engine start/stop control
- Enhanced stability and safety

Standard protection functions	Standard control functions	
Alternator protection - 2xReverse power - 2xOverload - 4xOvercurrent - 1xOvervoltage - 1xUndervoltage - 1xOver/underfrequency 1xUnbalanced current	**Powercontrol** - RPM control(synchronization) - Power control(grid connection) - Load share(island)	**Voltage control** - Voltage tracking (synchronization) - Voltage control(island) - PF control(grid connection) - Reactive power share (island）
	Lubrication control - Auto refilling - Warning and monitoring	**Pump control** - Cooling system - Emergency radiator
Busbar/mains protection - 1xOvervoltage - 1xUndervoltage - 1xOver/under frequency - 1xPhase sequence - 1xROCOF alarm	**Fan control** - Ventilation for engine room - Radiator fan - Emergency radiator fan	**Valve control** - Cooling system - Heating system - Emergency radiator
	Engine protection - Various routine and customized protection functions - Monitoring	

CG75-NG

Natural Gas CHP Unit

POWERLINK Power Systems
We Produce Green Energy...

Standard configuration

Engine	Alternator	Canopy and base	Electrical cabinet
Gas engine Ignition system Lambda controller Speed control system Electrical start motor Battery system Detonation control system Lockable isolator switch Turbocharger & intercooler Jacket water heater	AREP AC alternator H class insulation IP23 protection AVR voltage regulator PF control	Steel monocoque base frame Engine bracket Vibration isolators Alternator base	Air circuitbreaker PCC300 control system 10.4-inch touch screen Communication interfaces Breaker cabinet Mains floating charger Paralleling protection
Gas supply system	**Lubrication system**	**Standard voltage**	**Induction/ exhaust system**
Gas safety train Air/fuel mixer	Oil filter Daily auxiliary oil tank Auto refilling oil system New and waste oil tank (Only applicable to container)	380/220V 400/230V 415/240V 440/254V	Air filter Exhaust silencer Exhaust bellows Gas leakage protection(Only applicable to canopy and container)
Heat exchange system	**Service and documents**		
Exhaust/water heat exchanger Jacket water circulation pump Water/water heat exchanger Mixture circulation pump Expansion tank Heating circulation pump Three-way valves Intercoolerradiator	Tools package Installation and operation manual Maintenance manual Software manual Parts manual	Engine operation and maintenance manual Gas quality declaration Control system manual After service guide	

Optional configuration

Engine/Alternator	Electrical system	Gas supply system
Jacket water radiator Space heater Treatments against humidity and corrosion	RCD ATS control cabinet Thermal power gauge Electric power gauge	Gas flow gauge Emergency pressure relief torch Water separator Gas compressor Gas purification device
Voltage	**Exhaust system**	**Exhaust gas using**
220V 230V 240V	Three-way catalytic converter	Steam boiler LiBr refrigerator

Data is subject to change without prior notice as new products are always developed.
Please contact PowerLink or local agent with any doubts or for more information