

BES18S

ALL-IN-ONE ENERGY SYSTEM

SPECIFICATION



BES18S Battery/Solar/Diesel All-in-one Energy System

Item	Unit	Data		
Voltage	AC V	220	230	240
Max. output power	kVA/kW	21.6/21.6	21.6/21.6	21.6/21.6
Max. current	A	98	94	90
Continuous output power	kVA/kW	18/18	18/18	18/18
Continuous current	A	82	78	75
Overload capability		110% last 10mins, 120% last 1min (SOC>30%, AT<45°C)		
Frequency	Hz	50		
Phase	P	1		
Power factor	PF	1		
Dimensions	mm	2100 x 1150 x 1700		
Dry weight	kg	2000		
40' Loading	Qty	4		
Noise level(hybrid mode)	dBA@7m	55		
Noise level(battery mode)	dBA@7m	50		
Protection level		IP54		
Wind resistance rating		8		
Ambient temperature		-20°C-50°C		
Power connection input		AC socket Busbar		
Power connection output		Main load socket Busbar		
Certification standards		 UN38.3  IEC 62619  IEC 62477  IEC / EN 60529  EN 61000-6-1/2/3/4  AS 4777.2  G99 CE Declaration of Conformity Stage V		

Classified
Document
2026.06.03

The technical data is measured in standard conditions:

- Absolute atmospheric pressure: 100kPa
- Ambient temperature: 25°C
- Relative air humidity: 30%

Note: If the on-site operating environment changes, the parameters on the specification will change accordingly.

DC/AC System		
Rated power	kVA/kW	18/18
Output voltage	AC V	220/230/240
Parallel / On-grid function		Parallel: ☐ ; On-grid: ☒
MPPT rated power	kWp	18+18
Rated voltage	DC V	160-800

Grid Power Input		
Rated power	kVA/kW	18/18
Phase	P	1

PV System		
Solar panel voltage	DC V	22-60
Solar panel capacity	Wp	720x5

Battery System		
Battery type		LiFePO4
Battery capacity	kWh	21.1
Rated voltage	DC V	51.2
Cooling system		Liquid-cooled
Max charging rate		1C
Max discharging rate		1C
DOD (depth of discharge)		Default 80% (set via SOC)
NOTE: The discharge power decreases as the battery SOC decreases.		

Diesel Generation System		
Engine brand / mode		Yunnei / DEF20CFA4
Alternator brand		Powerlink
Rated power	kVA/kW	37/30
Rated voltage	AC V	240
Phase	P	1
Fuel tank capacity	L	100

Control System		
HMI control panel	inch	13" Touchscreen
Communication protocol		Modbus TCP/IP
Communication interface		WAN/WIFI/SIM
IoT		APP/WEB

Classified
Document
2026.06.03

* Data is subject to change without prior notice as new products are always developed.

Please contact POWERLINK or local agent with any doubts or for more information.